POWER EASE

POWEREASE 420 ENGINE

MODEL: 85.570.150

FEATURES

- Powerease engines have been used by BE Power Equipment for well over ten years and have proved themselves to be powerful and reliable. Their reputation has earned the trust to be used on a wide range of power equipment.
- Replacement engine for equipment that accepts a keyed, 1" horizontal shaft.
- Air cooled, 4-stroke, Over Head Valve (OHV) design enables higher compression ratio to obtain greater power output.
- Uses common SAE 10W30 motor oil to splash lubricate the components in the crankcase.
- Automatic low-oil sensor will shut down the engine if the oil level drops to dangerous levels.
- Fuel recommended to use is regular unleaded that is 86 octane or more. It is best to use fuel with no ethanol, but ethanol blends of up to 10% is acceptable.





Scan the QR code with your mobile device and discover more about this engine.

ENGINE SPECS

MODEL: TYPE: DISPLACEMENT: NET POWER: NET TORQUE: FUEL TYPE: MIN OCTANE: MAX ETHANOL: FUEL TANK CAPACITY: 6.1 L / 1.6 US GAL OII TYPE: OIL CAPACITY: LUBRICATION: COMPRESSION RATIO: 8.2:1 START SYSTEM: SHAFT TYPE: SHAFT ROTATION: VALVE CLEARANCES: .06" IN TAKE / .08" OUT TAKE

POWEREASE 420 AIR COOLED, 4-STROKE OHV 420CC 15 HP @ 3,600 RPM 17.8 FT/LB @ 2,500 RPM UNLEADED **86 OR MORE** 10% **SAF 10W30** 1.1L/1.16 US QTS FORCED SPLASH RECOIL **KEYED 1" HORIZONTAL** COUNTER CLOCKWISE

REPLACEMENT PARTS

AIR FILTER ELEMENT: AIR FILTER ASSEMBLY: MUFFLER ASSEMBLY: FUFI TANK: FUEL TANK CAP: FUEL TANK CAP STRAINER: 85.571.042 RECOIL ASSEMBLY: **IGNITION COIL:** ON/OFF SWITCH: OIL PLUG & DIPSTICK: CARBURETOR ASSEMBLY: 85.571.028 THROTTLE CONTROL KIT: CYCLINDER COVER: SPARK PLUG: AUTO LOW OIL SENSOR:

85.550.004 85.571.029E 85.571.030 85.571.031 85.571.013 85.571.026 85.571.032 85.571.008 85.571.025 85.571.137 85.571.022 85.519.001 85.571.003

BOXED	SIZE
I xWxH:	

WEIGHT:

17" x 18" x 18" 68 LBS

UNIT SIZE

17.75 16.25' 17.75

UNIT WEIGHT: 66 LBS

WARRANTY

	-
BASIC:	2 YEARS
REGISTERED:	5 YEARS
UPC:	777897146370

09-202

POWEREASE