POWER EASE

POWEREASE 740E ELECTRIC START ENGINE

MODEL: 85.578.220

FEATURES

- Powerease engines have been used by BE
 Power Equipment for well over ten years and
 have proved themselves to be powerful and
 reliable. Their reputation has earned the trust to
 be used on a wide range of power equipment.
- V-Twin cylinder design provides more power, lower vibration, longer life, and less maintenance than traditional single cylinder engines.
- Electric start harness with key system, starter motor and solenoid already set up makes starting the engine very easy.
- Replacement engine for equipment that accepts a keyed, 1" vertical shaft.
- Air cooled, 4-stroke, Over Head Valve (OHV)
 design enables higher compression ratio to
 obtain greater power output.
- Uses common SAE 10W30 motor oil to splash lubricate the components in the crankcase.
- Fuel recommended to use is regular unleaded that is 86 octane or more. It is best to use fuel with no ethanol, but ethanol blends of up to 10% is acceptable.



Scan the QR code with your mobile device and discover more about this engine.



ENGINE SPECS

MODEL: POWEREASE 740E

CYLINDERS: V-TWIN

TYPE: AIR COOLED, 4-STROKE OHV

DISPLACEMENT: **739CC**

NET POWER: **22.4 HP** @ **3,600 RPM**

NET TORQUE: 49 N*M/36.1 FT-LBS @ 2,500 RPM

FUEL TYPE: UNLEADED MIN OCTANE: 86 OR MORE

MAX ETHANOL: 10%

FUEL TANK: AUXILIARY
OIL TYPE: SAE 10W30
OIL CAPACITY: 2.0L/2.1 US QTS
LUBRICATION: FORCED SPLASH

COMPRESSION RATIO: 7.9:1

START SYSTEM: **ELECTRIC**

SHAFT TYPE: KEYED 1" VERTICAL SHAFT ROTATION: COUNTER CLOCKWISE

REPLACEMENT PARTS

CYLINDER HEAD GASKETS: 85.572.202 HEAD & EXHAUST GASKETS: 85.572.204 **FUEL STRAINER:** 85.572.208 FUEL PUMP ASSEMBLY: 85.572.205 OIL DIPSTICK: 85.572.200 STARTER MOTOR: 85.572.210 IGNITION COIL SET(2): 85.572.209 AIR CLEANER ELEMENT: 85.572.207 CARBURETOR ASSEMBLY: 85.572.206 SPARK PLUG SET(2): 85.572.203

BOXED SIZE

LxWxH: **22" x 22" x 21"**WEIGHT: **92 LBS**



UNIT WEIGHT: 86 LBS

WARRANTY

BASIC: 2 YEARS
REGISTERED: 5 YEARS
UPC: 777897343962

07-2022